

FDSN Web Service Specifications

Version 1.1 [Draft1](#)
2013/09/18

Purpose

To specify web service interfaces for the exchange of time series data, related metadata, event parameter and other data within the context of the International Federation of Digital Seismograph Networks (FDSN). The intention is to provide a specification that, when implemented at different FDSN data centers, can be used interchangeably by the same client software. The specification defines service names, query parameters and expected results.

List of service interfaces

dataselect – returns raw time series data in FDSN miniSEED format

station – returns metadata in FDSN StationXML [and alternate formats](#)

event – returns parametric data for events in QuakeML [and alternate formats](#)

Common service characteristics

Versioning

The services are versioned according the following three-digit (x.y.z) pattern:

SpecMajor.SpecMinor.Implementation

Where the fields have the following meaning:

SpecMajor: The major specification version, all implementations sharing this *SpecMajor* value will be backwards compatible with all prior releases. Values start at 1.

SpecMinor: The minor specification version, incremented when optional parameters or behavior is added to the previous specification but backwards compatibility is maintained with the previous major versions, i.e. all 1.# service versions will be compatible with version 1.0. Values start at 0.

Implementation: The implementation version, an integer identifier specific to the data center implementation. Useful to track service updates for bug fixes, etc. but with no implication on conformance to the specification.

Together the *SpecMajor* and *SpecMinor* versions imply [a minimum](#) expected behavior of a given service. This versioning scheme allows clients to expect specific behavior based on the *SpecMajor* version, while allowing the FDSN to extend the services with optional parameters while maintaining backwards compatibility. Each version number is service specific, there is no implication that *SpecMajor* version numbers across services are related.

Calling pattern

The services will be invoked using a subset of REST and HTTP methods. In particular all services will be invoked using the HTTP GET method whenever possible and the HTTP POST method for the few cases where the selection parameters are potentially large in size.

Service path and port

The following base URI pattern is to be used at each data center implementing FDSN services:

`<site>/fdsnws/<service>/<majorversion>/`

where **service** is one of *dataselect*, *station* or *event* and *SpecMajor* **version** is an integer value specifying the major specification version supported by the service. A **site** is the domain name of the data center hosting FDSN web services. For example the base URI for version 1 of the FDSN station service at ORFEUS might be:

`www.orfeus-eu.org/fdsnws/station/1/`

All services should be available on TCP/IP port 80.

Common Service methods

All services should support these common methods:

query – to submit a data or information request

version – to request the full service version (*SpecMajor.SpecMinor.Implementation*)

application.wadl – to request a WADL for the interface

Details of each method and further methods specific to a service are documented in the relevant service descriptions.

For example, submitting queries to the station service at ORFEUS would be performed using this URI:

`http://www.orfeus-eu.org/fdsnws/station/1/query?<key=value parameters>`

Similarly requesting the implementation version of the same service would be done using this URI:

`http://www.orfeus-eu.org/fdsnws/station/1/version`

which returns as simple text string indicating the software version, e.g. "1.2.8".

Requesting the WADL for a the same interface:

`http://www.orfeus-eu.org/fdsnws/station/1/application.wadl`

Minimum functionality

Implementations of these service interfaces should **support** all methods specified **as required**. Additionally, interfaces should conform to the calling patterns and expected results identified in this document to be considered **conformant** with the specification. Authentication methods are an exception, and only need to be supported by data centers that wish to require authentication for access to specific data sets.

Each service definition includes required and optional parameters; an implementation must support the required parameters to be considered conformant. The optional parameters supported by any given implementation should be specified in the WADL returned by the service.

Request URI construction

Request URIs to FDSN web services must not exceed 2000 bytes in length including the URL encoding; most common requests will be much shorter. Requests should be URL Encoded as a standard practice before submission to the service, but services should handle non-encoded submissions as far as is possible.

Common Service responses

General responses that should be used by all services are outlined below. Responses specific to each service are detailed in later sections.

No data selected

If a properly formatted request is submitted but would result in no data being returned to the user the service should return **HTTP status 204** (No Content) by default. Alternatively, the optional *nodata* parameter can be used to request that **HTTP status 404** (Not Found) be returned instead. A 404 status helps clarify situations where a 204 may be confusing, such as a web browser user, by including a message in the response. Clients should be aware that the 404 status code may be returned for error conditions such as problems with the web application or application container. Due to the multiple meanings for a 404 status, the 204 status is preferred for programmatic (non-browser) access.

Result set limitations

Limitations on the amount of information returned for any given request may be imposed independently for each service by each data center. If a client submits a request that would result in a data set beyond the service limit the service should return an **HTTP status 413** (Request Entity Too Large).

Errors messages

All errors reported to the client, either HTTP 4xx or 5xx status codes, should include an error message transmitted as MIME type **text/plain** using the following pattern:

Error <CODE>: <SIMPLE ERROR DESCRIPTION>

<MORE DETAILED ERROR DESCRIPTION>

Usage details are available from <SERVICE DOCUMENTATION URI>

Request:
<SUBMITTED URL>

Request Submitted:
<UTC DATE TIME>

Service version:
<3-LEVEL VERSION>

Common HTTP status codes

Table 1 includes a list of common status codes returned by FDSN web services. In most cases these will be the only codes returned by the services. Under error, maintenance or otherwise unusual conditions a client may receive other HTTP codes generated by web service containers, layer 7 routers (e.g. load balancers), firewalls, etc.

Table 1. Common HTTP status codes returned by FDSN services

Code	Description
200	Successful request, results follow
204	Request was properly formatted and submitted but no data matches the selection
400	Bad request due to improper specification, unrecognized parameter, parameter value out of range, etc.
401	Unauthorized, authentication required
403	Authentication failed or access blocked to restricted data
404	Alternate to 204 (set via the 'nodata' parameter), normally used for results returned to a web browser.
413	Request would result in too much data being returned, returned error message should include the service limitations in the detailed description. Service limits should also be documented in the service WADL.
414	Request URI too large
500	Internal server error
503	Service temporarily unavailable, used in maintenance and error conditions

Request parameters

The common and specific request parameters for each service are summarized in Table 1. In this Table, the **abbreviation** names are acceptable synonyms for the given **parameter** name. For a specific service and parameter group, each sub-group parameter set is exclusive; for example, for a call to the **fdsnws-station** service the client should supply a simple-time or window-time definition but not both. Service specific meanings for the parameters are described later in this document.

Table 1. Parameter specifications for FDSN web services, including applicable services for each group in italics.

Group	Subgroup	Parameter	Abbreviation	Default	Minimum	Maximum	Type	Units
time constraints								
	simple-time	<i>fdsnws-dataselect, fdsnws-station, fdsnws-event</i>						
		starttime	start	[Any]	[Any Valid Time]		time	UTC
		endtime	end	[Any]	[Any Valid Time]		time	UTC
	window-time	<i>fdsnws-station</i>						
		startbefore		[Any]	[Any Valid Time]		time	UTC
		startafter		[Any]	[Any Valid Time]		time	UTC
		endbefore		[Any]	[Any Valid Time]		time	UTC
		endafter		[Any]	[Any Valid Time]		time	UTC
channel constraints								
		<i>fdsnws-dataselect, fdsnws-station</i>						
		network	net	[Any]	[Valid ASCII or * or ?]		string	[Not Applicable]
		station	sta	[Any]	[Valid ASCII or * or ?]		string	[Not Applicable]
		location	loc	[Any]	[Valid ASCII or * or ?]		string	[Not Applicable]
		channel	cha	[Any]	[Valid ASCII or * or ?]		string	[Not Applicable]
geographic constraints								
	area-rectangle	<i>fdsnws-station, fdsnws-event</i>						
		minlatitude	minlat	-90.0	-90.0	90.0	float	degrees
		maxlatitude	maxlat	90.0	-90.0	90.0	float	degrees
		minlongitude	minlon	-180.0	-180.0	180.0	float	degrees
		maxlongitude	maxlon	180.0	-180.0	180.0	float	degrees
	area-circle	<i>fdsnws-station, fdsnws-event</i>						
		latitude	lat	0.0	-90.0	90.0	float	degrees
		longitude	lon	0.0	-180.0	180.0	float	degrees
		minradius		0.0	0.0	180.0	float	degrees
		maxradius		180.0	0.0	180.0	float	degrees
output control								
		<i>fdsnws-dataselect, fdsnws-station, fdsnws-event</i>						
		format		xml or miniseed	One of: <i>xml, miniseed</i> or <i>text</i>		string	[Not Applicable]
		nodata		204	One of: <i>204</i> or <i>404</i>		string	[Not Applicable]
service-specific constraints								
		<i>fdsnws-station</i>						
		level		station	One of: <i>network, station, channel</i> or <i>response</i>		string	[Not Applicable]
		includerestricted		TRUE	[Not Applicable]		boolean	[Not Applicable]
		includeavailability		FALSE	[Not Applicable]		boolean	[Not Applicable]
		updatedafter		[ANY]	[Any Valid Time]		time	UTC
		matchtimeseries		FALSE	[Not Applicable]		boolean	[Not Applicable]
		<i>fdsnws-event</i>						
		mindepth		[Any]	[Any]	[Any]	float	kilometers
		maxdepth		[Any]	[Any]	[Any]	float	kilometers
		minmagnitude	minmag	[Any]	[Any]	[Any]	float	Defined by the mag type
		maxmagnitude	maxmag	[Any]	[Any]	[Any]	float	
		magnitudetype	magtype	[Any]	[Not Applicable]		string	[Not Applicable]
		includeallorigins		FALSE	[Not Applicable]		boolean	[Not Applicable]
		includeallmagnitudes		FALSE	[Not Applicable]		boolean	[Not Applicable]
		includearrivals		FALSE	[Not Applicable]		boolean	[Not Applicable]
		eventid		[Any]	[Not Applicable]		string	[Not Applicable]
		limit		[Any]	0	[Any Positive]	integer	[Not Applicable]
		offset		1	1	[Any Positive]	integer	[Not Applicable]
		orderby		time	One of: <i>time, time-asc, magnitude</i> or <i>magnitude-asc</i>		integer	[Not Applicable]
		contributor		[Any]	[Not Applicable]		string	[Not Applicable]
		catalog		[Any]	[Not Applicable]		string	[Not Applicable]
		updatedafter		[Any]	[Any Valid Time]		time	UTC

Wildcards and lists in channel constraints parameters

The channel constraint parameters (network, station, location and channel) may include two specific wildcard characters with the following meaning:

- * – Matches zero to many characters
- ? – Matches any single character

The channel constraint parameters may also be submitted as comma-separated lists in order to select two or more values with a single request. For example, the channel parameter may be used to specify multiple channels:

channel=LHE,LHN,LHZ,BHZ (the individual values may also include wildcards)

Time parameter values

All **time** values are specified in UTC and should use one particular variation of the ISO 8601 standard with the addition of sub-seconds:

YYYY-MM-DDTHH:MM:SS.ssssss

Where the fields are as specified in ISO 8601 and a “T” separates the date and time. The “**ssssss**” are the sub-seconds expressed between 1/10 of a second to microsecond resolution; they do not all need to be present.

Two shorter variations for specifying time should be supported:

YYYY-MM-DDTHH:MM:SS (implies a time of **YYYY-MM-DDTHH:MM:SS.000000**)

where the sub-seconds are interpreted to be zeros and

YYYY-MM-DD (implies a time of **YYYY-MM-DDT00:00:00.000000**)

where the hour, minute, second and sub-second are interpreted to be zeros.

Time parameter interpretation

The *starttime* parameter should be interpreted as selecting any data or information (time series samples, earthquake origins, metadata epochs) at times on or later than the value specified.

Similarly, the *endtime* selects any data or information at times on or prior to the value specified.

The selection shall include any metadata epochs intersecting with the specified time range.

The *startbefore*, *startafter*, *endbefore* and *endafter* parameters, used only for the **fdsnws-station** service, specify the selection of information strictly starting or ending before or after a specified time value; they do not match any information occurring exactly at the time specified. These selection parameters are specifically for metadata and are useful for matching information that would otherwise be difficult with the other time parameters.

String, float, Boolean and integer parameter types

String type parameters may include ASCII characters, including the asterisk (*) and question mark (?) that have special meaning as wildcards for specific parameters.

Float type parameters should be specified in decimal notation, for example 98.1023. Scientific notation using an exponent or other representations will not accepted and should generate errors.

Boolean type parameters should be specified as either TRUE or FALSE, case insensitive.

Integer type parameters should be specified in decimal notation without a decimal point, exponential or other notation.

Blank SEED location identifier selection

Blank or empty location identifiers are encoded in SEED as two space characters (ASCII decimal 32). These may be specified by setting the *location* parameter to a string of two spaces, but care must be taken to properly encode the URI. For clarity and convenience, blank SEED location identifiers may also be specified by setting the *location* parameter to "--" (two dashes) which the service should translate to two space characters as needed.

fdsnws-dataselect version 1.1

The following methods shall be supported by the service:

query – to submit a data request

queryauth – to authenticate and submit a data request

version – to request the full service version number

application.wadl – to request a WADL for the interface

Requests using the **query** method:

The service shall accept requests formulated using the selection parameters identified in Table 1: *simple-time*, *channel constraints* and parameters specific to **fdsnws-dataselect**. Table 2 contains parameter descriptions for this service.

Table 2. Parameter descriptions for the **fdsnws-dataselect** service

Parameter	Required	Description
starttime	Yes	Limit results to time series samples on or after the specified start time
endtime	Yes	Limit results to time series samples on or before the specified end time
network	Yes	Select one or more network codes. Can be SEED network codes or data center defined codes. Multiple codes are comma-separated.
station	Yes	Select one or more SEED station codes. Multiple codes are comma-separated.
location	Yes	Select one or more SEED location identifiers. Multiple identifiers are comma-separated. As a special case "--" (two dashes) will be translated to a string of two space characters to match blank location IDs.
channel	Yes	Select one or more SEED channel codes. Multiple codes are comma-separated.
quality	No	Select a specific SEED quality indicator, handling is data center dependent.
minimumlength	No	Limit results to continuous data segments of a minimum length specified in seconds.
longestonly	No	Limit results to the longest continuous segment per channel.
format	No	Specify format of result, the default value is 'miniseed'.
nodata	No	Select status code for "no data", either '204' (default) or '404'.

These parameters may be submitted using either of the HTTP GET or POST methods. The POST method is useful to allow a large number of request parameters to be submitted.

For the GET method, the parameters should be submitted as key=value pairs and may not be specified more than once; if a parameter is submitted multiple times the result is undefined.

For the POST method, all parameters must be submitted as part of the POST body. The *quality*, *minimumlength* and *longestonly* parameters should be specified as key=value pairs on separate lines and the *simple-time* and *channel constraints* parameters repeated as many times as necessary following this pattern:

```
quality=M
minimumlength=0.0
longestonly=FALSE
NET STA LOC CHA STARTTIME ENDTIME
NET STA LOC CHA STARTTIME ENDTIME
NET STA LOC CHA STARTTIME ENDTIME
```

This would be POSTed to the URI "<site>/fdsnws/dataselect/1/query".

All rules for parameters apply equally whether specified using the GET or POST methods with the exception of blank location IDs, which must be specified as "--" in the POST body due to spaces being used as the field separator.

Responses for the *query* method:

The results of a successful request **shall** be returned as a stream of miniSEED **by default**, using the MIME type **application/vnd.fdsn.mseed**. The exact nature of the miniSEED returned by this service is data center dependent, a center may choose to remove duplicated data or prune to the exact window specified by the caller. The time series is generally expected to represent unprocessed, “raw” recorded data as supplied by the network operator or data owner. **A data center may choose to return the results in alternate formats as specified by the format parameter.**

Behavior for the *queryauth* method

HTTP Digest Authentication (RFC 2617) should be requested from the client. After successful authentication, a request should be accepted and handled as per the *query* method. Authentication credentials (user database and associated licensing schemes) are data center specific.

Behavior for the *version* method

The service shall return the implementation version as a simple text string using the MIME type **text/plain**. Any parameters submitted with the method will be ignored.

Behavior for the *application.wadl* method

The service shall return a WADL conformant description of the interface using the MIME type **application/xml**. Any parameters submitted with the method will be ignored. **The WADL shall describe all parameters supported by the interface and is primarily used to document which optional parameters are supported.**

Behavior for the *error* conditions

All errors returned to the client **shall** use the type and pattern described in the Common Service Responses section.

Examples

Requesting all data channels from IU station COLA for the first 12 hours of year 2012 using a GET request:

<http://service.iris.edu/fdsnws/dataselect/1/query?network=IU&station=COLA&starttime=2012-01-01T00:00:00&endtime=2012-01-01T12:00:00>

Requesting all LHE, LHN, LHZ data channels from IU station COLA for the first 12 hours of year 2012 using a POST request:

<http://service.iris.edu/fdsnws/dataselect/1/query>

POST message body:

```
quality=M
IU COLA 00 LHE 2012-01-01T00:00:00 2012-01-01T12:00:00
IU COLA 00 LHN 2012-01-01T00:00:00 2012-01-01T12:00:00
IU COLA 00 LHZ 2012-01-01T00:00:00 2012-01-01T12:00:00
```

fdsnws-station version 1.1

The following methods shall be supported by the service:

query – to submit a data request

version – to request the full service version number

application.wadl – to request a WADL for the interface

Requests using the *query* method:

The service shall accept requests formulated using the selection parameters identified in Table 1: *time constraints, channel constraints, geographic constraints* and the parameters listed that are specific for **fdsnws-station**. Table 3 contains parameter descriptions for this service.

Table 3. Parameter descriptions for the **fdsnws-station** service

Parameter	Required	Description
starttime	Yes	Limit to metadata epochs starting on or after the specified start time.
endtime	Yes	Limit to metadata epochs ending on or before the specified end time.
startbefore	No	Limit to metadata epochs starting before specified time.
startafter	No	Limit to metadata epochs starting after specified time.
endbefore	No	Limit to metadata epochs ending before specified time.
endafter	No	Limit to metadata epochs ending after specified time.
network	Yes	Select one or more network codes. Can be SEED network codes or data center defined codes. Multiple codes are comma-separated.
station	Yes	Select one or more SEED station codes. Multiple codes are comma-separated.
location	Yes	Select one or more SEED location identifiers. Multiple identifiers are comma-separated. As a special case "--" (two dashes) will be translated to a string of two space characters to match blank location IDs.
channel	Yes	Select one or more SEED channel codes. Multiple codes are comma-separated.
minlatitude	Yes	Limit to stations with a latitude larger than <u>or equal to</u> the specified minimum.
maxlatitude	Yes	Limit to stations with a latitude smaller than <u>or equal to</u> the specified maximum.
minlongitude	Yes	Limit to stations with a longitude larger than <u>or equal to</u> the specified minimum.
maxlongitude	Yes	Limit to stations with a longitude smaller than <u>or equal to</u> the specified maximum.
latitude	No	Specify the latitude to be used for a radius search.
longitude	No	Specify the longitude to be used for a radius search.
minradius	No	Limit results to stations within the specified minimum number of degrees from the geographic point defined by the latitude and longitude parameters.
maxradius	No	Limit results to stations within the specified maximum number of degrees from the geographic point defined by the latitude and longitude parameters.
level	Yes	Specify the level of detail for the results.
includerestricted	No	Specify if results should include information for restricted stations.
includeavailability	No	Specify if results should include information about time series data availability.
updatedafter	No *	Limit to metadata updated after specified date; updates are data center specific. * While this option is not required it is highly recommended due to usefulness.
matchtimeseries	No	Limit to metadata where selection matches time series data availability.
format	No	Specify format of result, either 'xml' (default) or 'text' (defined below).
nodata	No	Select status code for "no data", either '204' (default) or '404'.

These parameters may be submitted using either of the HTTP GET or POST methods. The POST method is useful to allow a large number of core request parameters to be submitted.

For the GET method, the parameters should be submitted as key=value pairs and may not be specified more than once; if a parameter is submitted multiple times the result is undefined.

For the POST method, all parameters must be submitted as part of the POST body. The parameters for *network*, *station*, *location*, *channel*, *starttime* and *endtime* may be repeated as many times as necessary, all other parameters should be specified as key=value pairs on separate lines following this pattern:

```
parameter1=value  
parameter2=value  
NET STA LOC CHA STARTTIME ENDTIME  
NET STA LOC CHA STARTTIME ENDTIME  
NET STA LOC CHA STARTTIME ENDTIME
```

This would be POSTed to the URI "<site>/fdsnws/station/1/query".

All rules for parameters apply equally whether specified using the GET or POST methods with the exception of blank location IDs, which must be specified as "--" in the POST body due to spaces being used as the field separator.

Controlling the level of detail

The *level* parameter controls the amount of detail included in the returned FDSN StationXML results with the following hierarchy: network, station, channel and response. For example, if the station level is requested the Station elements will be included in the results but not Channel or Response related information.

Responses for the *query* method:

The results of a successful request shall be returned as FDSN StationXML using MIME type **application/xml** by default or when the *format* parameter value is 'xml'. If the *format* parameter value is 'text' the results shall be returned in a simple ASCII format for *level* = network, station or channel using MIME type **text/plain** as defined below. Requests for text output at the response level should generate an error.

Behavior for the *version* method

The service shall return the return the implementation version as a simple text string using the MIME type **text/plain**. Any parameters submitted with the method will be ignored.

Behavior for the *application.wadl* method

The service shall return a WADL conformant description of the interface using the MIME type **application/xml**. Any parameters submitted with the method will be ignored. The WADL shall describe all parameters supported by the interface and is primarily used to document which optional parameters are supported.

Behavior for the *error* conditions

All errors returned to the client shall use the type and pattern described in the Common Service Responses section.

Text output formats for network, station and channel levels

These simple text output formats contain one entry per line with common fields separated by vertical bar characters ("|": ASCII decimal 124). Lines beginning with a hash character ("#": ASCII decimal 35) should be considered comment lines.

level=network

Network	Description	StartTime	EndTime	TotalStations
Network	Description	StartTime	EndTime	TotalStations

...

level=station

Network	Station	Latitude	Longitude	Elevation	StartTime	EndTime
Network	Station	Latitude	Longitude	Elevation	StartTime	EndTime

...

level=channel

Network	Station	Location	Channel	Latitude	Longitude	Elevation	Depth	Azimuth	Dip	Instrument	Scale	ScaleFrequency	ScaleUnits	SampleRate	StartTime	EndTime
Network	Station	Location	Channel	Latitude	Longitude	Elevation	Depth	Azimuth	Dip	Instrument	Scale	ScaleFrequency	ScaleUnits	SampleRate	StartTime	EndTime

...

In the level=channel output, the Scale value is the total sensitivity, the ScaleFrequency is the frequency at which the Scale is valid and the ScaleUnits are the units of data after the Scale value has been applied. These values are equivalent to the values in the StationXML <InstrumentSensitivity> structure or stage 0 of SEED headers.

Examples

Requesting metadata for all channels from IU station COLA with no time limitations:

<http://service.iris.edu/fdsnws/station/1/query?network=IU&station=COLA&level=channel>

Requesting metadata for all BH* channels between latitude -10 and -45 and longitude between 112 and 155 (e.g. Australia):

http://service.iris.edu/fdsnws/station/1/query?channel=BH*&maxlatitude=-10&minlatitude=-45&minlongitude=122&maxlongitude=155&level=channel

Requesting metadata in simple text format at the network level:

<http://service.iris.edu/fdsnws/station/1/query?network=II,IU&format=text&level=network>

#Network	Description	StartTime	EndTime	TotalStations
II	Global Seismograph Network (GSN - IRIS/IDA)	1986-01-01T00:00:00	2500-12-12T23:59:59	50
IU	Global Seismograph Network (GSN - IRIS/USGS)	1988-01-01T00:00:00	2500-12-12T23:59:59	255

Requesting metadata in simple text format at the station level:

<http://service.iris.edu/fdsnws/station/1/query?network=IU&format=text&level=station>

#	Network	Station	Latitude	Longitude	Elevation	SiteName	StartTime	EndTime
IU	ANMO	34.9459	-106.4572	1850.0	Albuquerque, New Mexico, USA	1989-08-29T00:00:00	1995-07-14T00:00:00	
IU	ANMO	34.9459	-106.4572	1850.0	Albuquerque, New Mexico, USA	1995-07-14T00:00:00	2000-10-19T16:00:00	
IU	ANMO	34.9502	-106.4602	1839.0	Albuquerque, New Mexico, USA	2000-10-19T16:00:00	2002-11-19T21:07:00	
...								

Requesting metadata in simple text format at the channel level:

<http://service.iris.edu/fdsnws/station/1/query?station=COLA&format=text&level=channel>

#	Network	Station	Location	Channel	Latitude	Longitude	Elevation	Depth	Azimuth	Dip	Instrument	Scale	ScaleFreq	ScaleUnits	SampleRate	StartTime	EndTime
IU	COLA	20	HNE		64.873599	-147.8616	200.0	0.0	90.0	0.0	Kinematics FBA-23 Low-Gain Sensor	53687.1	1.0	M/S**2	80.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	20	HNN		64.873599	-147.8616	200.0	0.0	0.0	0.0	Kinematics FBA-23 Low-Gain Sensor	53687.1	1.0	M/S**2	80.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	20	HNZ		64.873599	-147.8616	200.0	0.0	0.0	-90.0	Kinematics FBA-23 Low-Gain Sensor	53687.1	1.0	M/S**2	80.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	20	LNE		64.873599	-147.8616	200.0	0.0	90.0	0.0	Kinematics FBA-23 Low-Gain Sensor	53435.4	0.02	M/S**2	1.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	20	LNN		64.873599	-147.8616	200.0	0.0	0.0	0.0	Kinematics FBA-23 Low-Gain Sensor	53435.4	0.02	M/S**2	1.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	20	LNZ		64.873599	-147.8616	200.0	0.0	0.0	-90.0	Kinematics FBA-23 Low-Gain Sensor	53435.4	0.02	M/S**2	1.0	2005-09-28T22:00:00	2009-07-08T22:00:00
IU	COLA	00	BH1		64.873599	-147.8616	80.0	120.0	111.0	0.0	Geotech KS-54000 Borehole Seismometer	8.04479E8	0.02	M/S	20.0	2005-09-27T00:00:00	2009-07-08T22:00:00
IU	COLA	00	BH2		64.873599	-147.8616	80.0	120.0	201.0	0.0	Geotech KS-54000 Borehole Seismometer	8.1814E8	0.02	M/S	20.0	2005-09-27T00:00:00	2009-07-08T22:00:00
IU	COLA	00	BHZ		64.873599	-147.8616	80.0	120.0	0.0	-90.0	Geotech KS-54000 Borehole Seismometer	8.44329E8	0.02	M/S	20.0	2005-09-27T00:00:00	2009-07-08T22:00:00
...																	

Requesting two time windows of data for two IU stations with different channel selections using a POST request:

<http://service.iris.edu/fdsnws/station/1/query>

POST message body:

```
level=channel
includerestricted=FALSE
IU COLA 00 LH? 2012-01-01T00:00:00 2012-01-01T12:00:00
IU ANMO 10 BH? 2013-07-01T00:00:00 2013-02-07T12:00:00
```

fdsnws-event version 1.1

The following methods shall be supported by the service:

query – to submit a data request

catalogs – to submit a request for available catalogs

contributors – to submit a request for available contributors

version – to request the full service version number

application.wadl – to request a WADL for the interface

Requests using the **query** method:

The service shall accept requests formulated using the selection parameters identified in Table 1: *simple-time* and *geographic constraints* and the parameters listed that are specific for **fdsnws-event**. Table 4 contains parameter descriptions for this service.

Table 4. Parameter descriptions for the **fdsnws-event** service

Parameter	Required	Description
starttime	Yes	Limit to events on or after the specified start time.
endtime	Yes	Limit to events on or before the specified end time.
minlatitude	Yes	Limit to events with a latitude larger than <i>or equal to</i> the specified minimum.
maxlatitude	Yes	Limit to events with a latitude smaller than <i>or equal to</i> the specified maximum.
minlongitude	Yes	Limit to events with a longitude larger than <i>or equal to</i> the specified minimum.
maxlongitude	Yes	Limit to events with a longitude smaller than <i>or equal to</i> the specified maximum.
latitude	No	Specify the latitude to be used for a radius search.
longitude	No	Specify the longitude to be used for a radius search.
minradius	No	Limit to events within the specified minimum number of degrees from the geographic point defined by the latitude and longitude parameters.
maxradius	No	Limit to events within the specified maximum number of degrees from the geographic point defined by the latitude and longitude parameters.
mindepth	Yes	Limit to events with depth more than the specified minimum.
maxdepth	Yes	Limit to events with depth less than the specified maximum.
minmagnitude	Yes	Limit to events with a magnitude larger than the specified minimum.
maxmagnitude	Yes	Limit to events with a magnitude smaller than the specified maximum.
magnitudetype	No	Specify a magnitude type to use for testing the minimum and maximum limits.
includeallorigins	No	Specify if all origins for the event should be included, default is data center dependent but is suggested to be the preferred origin only.
includeallmagnitudes	No	Specify if all magnitudes for the event should be included, default is data center dependent but is suggested to be the preferred magnitude only.
includearrivals	No	Specify if phase arrivals should be included.
eventid	No	Select a specific event by ID; event identifiers are data center specific.
limit	No	Limit the results to the specified number of events.
offset	No	Return results starting at the event count specified, starting at 1.
orderby	Yes	Order the result by time or magnitude with the following possibilities: <i>time</i> : order by origin descending time <i>time-asc</i> : order by origin ascending time <i>magnitude</i> : order by descending magnitude <i>magnitude-asc</i> : order by ascending magnitude
catalog	No	Limit to events from a specified catalog
contributor	No	Limit to events contributed by a specified contributor.
updatedafter	No *	Limit to events updated after the specified time. * While this option is not required it is highly recommended due to usefulness.
format	No	Specify format of result, either 'xml' (default) or 'text' (defined below).
nodata	No	Select status code for "no data", either '204' (default) or '404'.

These parameters should be submitted as key=value pairs using the HTTP GET method and may not be specified more than once; if a parameter is submitted multiple times the result is undefined.

Responses for the *query* method:

The results of a successful request **shall** be returned as QuakeML 1.2 using MIME type **application/xml** by default or when the *format* parameter value is 'xml'. If the *format* parameter value is 'text' the results shall be returned in a simple ASCII format using MIME type **text/plain** as defined below.

Behavior for the *catalogs* method

The service shall return the return the list of available catalogs in the simple XML schema illustrated below using the MIME type **application/xml**. Any parameters submitted with the method will be ignored.

```
<Catalogs>
  <Catalog>EMSC</Catalog>
  <Catalog>GCMT</Catalog>
  <Catalog>NEIC PDE</Catalog>
  <Catalog>ISC</Catalog>
</Catalogs>
```

Behavior for the *contributors* method

The service shall return the return the list of available contributors in the simple XML schema illustrated below using the MIME type **application/xml**. Any parameters submitted with the method will be ignored.

```
<Contributors>
  <Contributor>NEIC</Contributor>
  <Contributor>EMSC</Contributor>
  <Contributor>ISC</Contributor>
</Contributors>
```

Behavior for the *version* method

The service shall return the return the implementation version as a simple text string using the MIME type **text/plain**. Any parameters submitted with the method will be ignored.

Behavior for the *application.wadl* method

The service shall return a WADL conformant description of the interface using the MIME type **application/xml**. Any parameters submitted with the method will be ignored. The WADL shall describe all parameters supported by the interface and is primarily used to document which optional parameters are supported.

Behavior for the *error* conditions

All errors returned to the client **shall** use the type and pattern described in the Common Service Responses section.

Text output format

This simple text output format contains one event per line with common fields separated by vertical bar characters (ASCII decimal 124).

EventID | Time | Latitude | Longitude | Depth/km | Author | Catalog | Contributor | ContributorID | MagType | Magnitude | MagAuthor | EventLocationName
EventID | Time | Latitude | Longitude | Depth/km | Author | Catalog | Contributor | ContributorID | MagType | Magnitude | MagAuthor | EventLocationName
...

Example

Requesting origins for all events above magnitude 6 in 2012:

<http://service.iris.edu/fdsnws/event/1/query?minmag=6&starttime=2012-01-01T00:00:00&endtime=2013-01-01T00:00:00>

References

SEED data format - http://www.iris.edu/manuals/SEEDManual_V2.4.pdf

QuakeML - <https://quake.ethz.ch/quakeml/>

FDSNStationXML - <http://www.fdsn.org/xml/station/>

Web Application Description Language (WADL) - <http://www.w3.org/Submission/wadl/>

Changes

2012/07/12 – Initial specification, release candidate 1

2012/07/18 – Remove <Total> elements from **catalog** and **contributor** XML responses for fdsnws-event. Designate the fdsnws-station specification as provisional until the FDSN StationXML schema is defined.

2012/11/20 – Include examples request URI's for each service, remove provisional status on fdsnws-station.

2013/04/24 – [Final edits for version 1.0](#)

- 1) Replace parameter name 'preferredonly' with 'includeallorigins' in the fdsnws-event section of Table 1 and make the default value FALSE. This now matches other references to the parameter names and was the original intention.
- 2) Change the example of exclusive parameter sub-groups to refer to fdsnws-station as a more appropriate illustration (page 4).
- 3) Add link to FDSN StationXML specification in references and remove provisional language.
- 4) Remove the DRAFT designation.

[2013/09/18 – Integrate proposed version 1.1 changes](#)

- 1) [Add designation of required versus optional parameters for each service interface.](#)
- 2) [Allow fdsnws-station to accept arbitrary selections via the POST method. Support for this method is required for all 1.1 implementations of fdsnws-station.](#)
- 3) [Add optional 'format' parameter to each service definition. The default formats of miniSEED, StationXML and QuakeML remain the same for each interface. For station and event, document an alternate, simple text format to return when format=text including examples.](#)
- 4) [Add optional 'nodata' parameter to each service definition that accepts values of '204' \(default\) and '404'. This parameter controls the HTTP status code to return when the request was successful but matched no data.](#)
- 5) [Add optional 'matchtimeseries' parameter to the fdsnws-station definition. This parameter is used to limit results to selections that match time series data availability.](#)
- 6) [Clarify definition of starttime and endtime parameters to explicitly include metadata epochs intersection with the specified time range.](#)
- 7) [Clarify definition of minimum and maximum latitude and longitude to be inclusive by adding "or equal to" to their description.](#)